

HOMAG + LIGMATECH KAL 330 /8/A20/S2 + ZHR

ONLINE MACHINE
PAGE



BRAND **HOMAG + LIGMATECH**

CODE **220700**

MODEL **KAL 330 /8/A20/S2 + ZHR**

TYPE **EDGE BANDER**

TECHNICAL DETAILS

A) SINGLE SIDE EDGE BANDER (Left)

Edges (tape) thickness in rolls (min/max) mm 0,3 - 3

Edges thickness in strips / lippings (min/max) mm 0,4 - 20

Panels thickness (min/max) mm 8 - 60

Numerical Control POWER Control PC 22

Spraying unit (Antisticking liquid)

Infeed fence, adjustable by N.C.

Panels infeed system

Pre-milling Unit (vertical joint trimmers) adjustable by N.C. type KAL 300 (Kw 3 x 2)

Glueing Unit (P.U.R. Glue + Quick Melt unit) PU 34 / QA 34

Band Pressure zone (adjustable by N.C.) "C"

Edge coils supporting unit, N° 6 reels

Snipping (endcutting) unit HL 86 Servo (Kw 0,4 x 2) 35 m/min

Rough Trimming unit Optimat (Kw 1,5 x 2)

Fine Trimming unit ALUKANTE (Kw 0,4 x 2) adjustable by N.C.

Spraying Unit (for sliding liquid)

Multi Function Unit (Profile contour Trimming unit) FK 13 Servo (Kw 0,4 x 2)

Profile edge scraping unit (Multiprofile, adjustable by N.C.) MN 21

Finish processing unit (Glue scraper + Buffing unit) FA 11

Spraying Unit (for polishing liquid)

B) Workpieces Return system "LIGMATECH" ZHR 05/L/095

PHOTOS



01



02

Photos

Code: 220700



03



04